

2PP of ORMOCERs will be used for the low-cost fabrication of artificial microstructured and nanostructured components for different applications in optics, medicine, and biology.

STEVEN TROHALAKI

### Microfluidic Plugs Produce Long-Period Gratings in Microstructured Optical Fiber

With the development of wavelength-division multiplexing, bandwidth has been significantly increased over the past few years, but for continued advancement, dynamic filters and attenuators need to be developed. Researchers at OFS Labora-

tories in New Jersey have developed a microstructured optical fiber (MOF) whose wavelength-dependent attenuation can be modified by a long-period grating, composed of an alternating air/liquid refractive index, in the cladding.

As described in the March 3 issue of *Applied Physics Letters*, C. Kerbage and B. Eggleton, who is now director of the photonics research center called CUDOS at the University of Sydney in Australia, have developed a method of alternately drawing fluid (in this study, trifluorotoluene) and air into the holes of the MOF. This is achieved by repeatedly dipping a cleaved fiber in a liquid reservoir

while subjected to a vacuum on the other end of the fiber. When the fiber is submerged, it draws in liquid, and when it is not submerged, it draws in air. In order to produce attenuation in the 1550-nm communications window, a duty cycle of 125 Hz was used, corresponding to a grating period of 460  $\mu\text{m}$ . While the microfluidic plugs are in the cladding of the fiber and should not strongly interact with the light propagating down the 8- $\mu\text{m}$ -diameter germanium-doped core, the fiber has been tapered to extend the single-mode field into the cladding. The higher-order modes in the cladding then interact with the periodic refractive-index mismatch, causing high losses at a determined wavelength. As the fiber tapers back to its original diameter and into the single-mode fiber, the higher order modes are attenuated while the fundamental mode continues to propagate.

While the use of long-period gratings is not a new technology in fiber optics, such gratings have lacked the degree of tunability of the MOF with microfluidic plugs. With both ends of the fiber coupled to a single-mode fiber, the ends of the MOF fiber can be heated, creating an expansion of the air in the ends of the fiber. The air between the microfluidic plugs is compressed, changing the period of the grating. The fiber then exhibits wavelength tunability. According to the researchers, this type of fiber holds promise for devices in optical communication and fiber sensing.

JEFFREY R. DiMAIO

### Research on Self-Assembled Monolayer Field-Effect Transistors Concludes Previous Reports are Implausible

Last year, much of J.H. Schön's innovative work at Lucent on field-effect transistors made from self-assembled dithiol monolayers was judged to be fraudulent by an independent review committee. However, questions remained within the molecular electronics community as to which, if any, of the results of Schön's discredited research could be achieved. Recently, a group of researchers from IBM T.J. Watson Research Center have investigated Schön's system to elucidate the limitations and the key requirements necessary to fabricate molecular devices. While the researchers were unable to reproduce Schön's results, they identified some of the design rules necessary to fabricate molecular devices, which include the high purity of molecules for self-assembly and a thorough characterization of the surfaces at each step of the fabrication on both molecular and device-area levels. The researchers also determined that the molecular-device structure must be characterized both structurally and electrically. In addition, the research team explained that tunneling places a lower limit on channel length, and therefore molecular length, to  $\sim 3$  nm. In addition, electrostatics requires gate dielectrics with thicknesses of less than 2/3 the molecular length, although they are also subject to tunneling limitations.

As reported in the February issue of *Nano Letters*, C.R. Kagan and co-workers created prototypes of the devices having the structure of field-effect transistors ("trench" and planar Si structures) with self-assembled monolayers of 1,1'-biphenyl-4,4'-dithiol instead of an inorganic semiconductor. The prototypes were studied in detail after each step of preparation. The geometry of the devices on Si wafers was fabricated using lithography, reactive-ion etching, and anisotropic wet-etching techniques. After this, a uniform film of gate dielectric was formed. Source and drain electrodes were prepared by collimated evaporation of Au and Ti on the gate dielectric. Self-assembled monolayers of dithiols formed on the source electrodes were characterized by local imaging probes such as scanning tunneling and atomic force microscopies, as well as large-area characterization by, for example, contact-angle measurements and ellipsometry.

The researchers found that biphenylmonothiol and biphenyldithiol form disordered layers with, at best, small ( $\sim 10$  Å) ordered regions, and that molecules such as alkanethiols assemble to form ordered domains separated by disordered boundaries. The devices made of the well-washed monolayers of 1,1'-biphenyl-4,4'-dithiol formed electrical shorts, contrary to the characteristics reported by Schön, but consistent with the expected physics for these disordered, short molecule assemblies.

In efforts to uncover the origin of the  $I$ - $V$  characteristics reported by Schön, the IBM research team formed molecular multilayers with longer channel lengths. The researchers, however, did not observe significant gate field effect; furthermore, they found that obtaining significant field effect and turning the device off are fundamentally impossible. Despite the evidence of recent misconduct, though, the research team said that "there is no scientific reason to lose faith in the tremendous promise of this field."

An exploration of Schön's work was also carried out by a research team in The Netherlands; see the MRS Web site at [www.mrs.org/gateway/matl\\_news.html](http://www.mrs.org/gateway/matl_news.html).

MAXIM NIKIFOROV

### X-Rays Generated Using Graphite Nanofiber Cold Cathode with Copper Anode

X-ray imaging has numerous technological and medical uses. To produce x-rays, typically a heated cathode emits electrons by thermionic emission (TE); the electrons then accelerate through a high potential difference before they bombard a metal target anode. The hot-cathode method has several drawbacks, such as the short lifetime of the hot cathode as it reacts with residual gases and the low efficiency of the TE process. In the March 10 issue of *Applied Physics Letters*, researchers report the creation of a point x-ray source using a graphite nanofiber (GNF) cold cathode and a conical copper anode, yielding a high-resolution x-ray radiography system and thus eliminating the need for a cooling system required for hot-cathode sources.

The GNFs were grown on a hot steel plate by thermal chemical vapor deposition from CO and hydrogen. From their analysis of the diffraction pattern observed

with transmission electron microscopy, the researchers conclude that the GNF cathode consisted of large numbers of fibers that were about 50 nm in diameter but were not carbon nanotubes. Electrons were drawn from the cold GNF cathode through field emission; that is, a strong electric field between the GNF cathode and the Cu anode pulled the electrons off. The researchers, T. Matsumoto of Stanley Electric Corp. in Yokohama, Japan, and H. Mimura of Tohoku University in Sendai, Japan, chose a simple diode configuration (instead of the usual triode), not only for its superior x-ray generation efficiency but also for its potential advantages in size and cost. To assure that the x-rays would emerge from a point, they restricted the electron bombardment region of the Cu anode by coating all but about 10  $\mu\text{m}$  of the sharpened metal tip with an insulating silicate.

Mastumoto and Mimura investigated the current-voltage characteristics of the efficient GNF cathode and also spectrally characterized the point source's x-ray output using a Ge detector and a multichannel analyzer. Next, they imaged a tungsten mesh and a Pb x-ray test chart in the transmission geometry, where the test object is between the x-ray source and the detector (a charge-coupled device camera with a NaI scintillator). The system achieved a high resolution, roughly 10  $\mu\text{m}$ , with an image acquisition time of 10 s using a charge-coupled device.

"There is great interest in building a practical, efficient, high-current-density x-ray device," said Matsumoto, "and we've now developed a simple x-ray radiography system. Since the efficient field-emission process eliminates the usual bulky water-cooling system, this makes possible a portable, compact x-ray system."

RICHARD LOUIE

### Incorporation of Particle Size Distribution Simplifies Modeling of SiCN Powder Oxidation Kinetics

The oxidation kinetics of polymer-derived ceramic materials is often studied using powdered samples because of the difficulty in obtaining dense specimens. The change in sample mass is measured as a function of time, and the data is fitted to a parabolic oxidation model. To simplify data analysis, the powder sample is treated as an assembly of perfectly spherical particles with identical radii. The monosize model results in significant errors in the value of the rate constant obtained from the measurement. Recently, R. Raj, A. Saha, and S. Shah of

the Department of Mechanical Engineering at the University of Colorado, Boulder, have developed a model that accounts for the particle size distribution in the powder. Application of this statistical model to the time-dependent oxidation of silicon carbonitride (SiCN) yielded a much more accurate value of the rate constant than that provided by the monosize model. According to Raj, "This improved data analysis technique gives much greater credibility to the simple experimental approach of using powders to study material oxidation rates."

As described in the February issue of the *Journal of the American Ceramic Society*, the researchers prepared SiCN powder by cross-linking and pyrolyzing Cereset-SN, a commercially available precursor. The final product was crushed into powder and imaged using scanning electron microscopy. Size measurements from the micrographs were used to generate a histogram of radius values and an average radius value. The SiCN was oxidized in air at 1350°C for 150 h, with the mass of the sample recorded periodically throughout the process. The monosize and statistical models were then fitted to this data.

Data analysis with the monosize

model yielded two limiting values for the oxidation rate constant because one rate constant was needed to fit the data for short-term oxidation kinetics and the other for long-term oxidation. In this study, this parabolic rate constant  $k_p$  was found to lie in the range  $19.7 \times 10^{-18} \text{ m}^2/\text{s} < k_p < 2.7 \times 10^{-18} \text{ m}^2/\text{s}$ . The statistical analysis, on the other hand, resulted in a theoretical curve that fit the entire time span of the data, using only one value of the rate constant  $4.5 \times 10^{-18} \text{ m}^2/\text{s}$  in this study, which greatly improved the accuracy of rate constant determination.

Raj is currently developing a statistical model that will account for the distribution in the particle shape as well as size. Current models assume a spherical particle shape.

GREG KHITROV

### Emitting Amorphous Molecular Materials for Electroluminescence Designed

Recently, amorphous molecular materials have received a great deal of attention as a new class of functional organic materials because of their isotropic properties, due to the absence of grain boundaries, and ease of uniform film formation. In the



#### MASSACHUSETTS INSTITUTE OF TECHNOLOGY

Join us this summer for in-depth weeklong programs designed for professionals and executives, including:

**2.34s Mechanics of Elastomeric and Elastomeric-Like Materials**

Mary C. Boyce  
June 23 – June 25

**2.65s Fuel Cells and Batteries: Electrochemical Energy Conversion and Storage**

Ernst G. Crauhalho, Yang Shao-Horn  
August 4 – August 8

**6.17s Physics and Technology of Organic Optoelectronic Devices**

Marc Baldo, Vladimir Bulovic  
June 16 – June 20

**16.38s Fundamentals of Lasers, Fiberoptics and Their Unique Applications**

Shaoul Ezekiel  
July 14 – July 18

**16.60s Multidisciplinary System Design Optimization**

Oliver L. de Weck, Karen E. Willcox  
June 16–June 20

**16.90s Principles of Optical Sensors**

Shaoul Ezekiel  
July 28 – August 1

**20.02s Advances in Controlled Release Technology**

Robert S. Langer  
June 23 – June 27

**20.05s Biomaterials And Stem Cells Two Disciplines to Build Functional Tissues in Vitro**

Carlos E. Semino  
June 16– June 20

**PST105s Fiber Reinforced Composite Materials**

Frederick J. McGarry  
July 21 – July 25

For a complete list, visit:

[HTTP://WEB.MIT.EDU/PROFESSIONAL](http://web.mit.edu/professional)

MIT Professional Institute  
77 Massachusetts Ave., Room 9-435,  
Cambridge, MA 02139  
Phone 617-253-2101 • Fax 617-253-8042  
Email: [professional-institute@mit.edu](mailto:professional-institute@mit.edu)

Interested in extending your study  
at MIT to a semester or a year?  
Develop a custom program:  
[HTTP://WEB.MIT.EDU/ADVANCEDSTUDY](http://web.mit.edu/advancedstudy)

For more information, see <http://advertisers.mrs.org>