

ERRATUM

GNSS IF Signal Simulation Considering Oscillator Phase Noise – ERRATUM

Bing Xu and Lei Dou

[doi:10.1017/S0373463318000036](https://doi.org/10.1017/S0373463318000036), Published by Cambridge University Press, 05 February 2018.

The Editor and Publishers regret that the following typographical errors have been made to Xu and Dou (2018), and the corrections below should be considered when reading the paper.

Table 3: Replace caption with: “Table 3. Measured ADEVs for $B_n = 10$ Hz and percentage errors.”

Page 9: Third line from the bottom replace “ $B_n = 1$ kHz” with “ $B_n = 1$ kHz”.

Table 4: Replace caption with: “Table 4. Measured ADEVs for $B_n = 1$ kHz and percentage errors.”

Table 5: Replace caption with: “Table 5. Filtered ADEVs for $B_n = 1$ kHz and percentage errors.”

Equation (15) (Page 11): Replace with the following equation:

$$\sigma_A = \frac{180}{\pi} \sqrt{2\pi^2 f_{RF}^2 \left(\frac{\pi^2 h_{-2}}{\sqrt{2}\omega_L^3} + \frac{\pi h_{-1}}{4\omega_L^2} + \frac{h_0}{4\sqrt{2}\omega_L} \right)} \text{(degree)}$$

REFERENCE

Xu, B. and Dou, L. GNSS IF Signal Simulation Considering Oscillator Phase Noise. *The Journal of Navigation*, Published by Cambridge University Press, 5 February 2018. [doi:10.1017/S0373463318000036](https://doi.org/10.1017/S0373463318000036).